

Univers	Professional
Type	Verticality
Category	Anchors
Subcategory	Rock and concrete anchors



COLLINOX

Forged stainless steel glue-in bolt.

Short Description	Forged stainless steel glue-in bolt (pack of 10)
-------------------	--

Selling Points	• 10 x 70 mm
----------------	--

Note: Items sold in packs are not marked for individual resale.

Specification	• Material(s): forged stainless steel • Certification(s): EN 959
---------------	--

Specifications by reference

Reference(s)	G100AA00
Diameter	10 mm
Weight	95 g
	Granite, gneiss higher than 80 MPa: preliminary testing recommended
	Hard limestone higher than 80 MPa: preliminary testing recommended Limestone and medium sandstone 80 MPa to 45 MPa: preliminary testing recommended
	Soft rock (soft sandstone, limestone) lower than 45 MPa: preliminary testing required
	Very high quality concrete (civil engineering structure) higher than 50 MPa: preliminary testing recommended
	Medium quality concrete from 25 to 50 MPa: preliminary testing recommended
Length	7 cm
Drilling depth	7-7,5 cm
Drilling diameter	12 mm
Type of installation	G101AA00 glue (or other glues approved by Petzl)
Suggested drying time	40 min - 10 h
Shear strength in 50 MPa concrete	25 kN
Pull-out strength in concrete 50 MPa	15 kN
	Times are given for G101AA00 glue (times may vary depending on the glue used and on the external environment)
Made in	FR
Guarantee	3 years
Inner Pack Count	1
Quantity Per Box	2
EAN	3342540829817

Related product(s) AMPOULE COLLINOX