


Univers	Professional
Type	Verticality
Category	Ropes
Subcategory	Low stretch kernmantel ropes




CONTROL 12.5 mm

The CONTROL 12.5 mm low stretch kernmantle rope is designed for tree care. The large diameter provides great strength and excellent grip. EverFlex technology provides great flexibility and excellent handling over time. It comes with a splice at one or two ends, for optimal rope glide through devices like a friction saver or pulley, and through tree branches. With a small splice, the rope can pass through the friction chain of the ZIGZAG and ZIGZAG PLUS mechanical Prusiks. The rope is available in two colors and three lengths with one splice, and one length with two splices.



The rope's construction provides optimal performance when used with the ZIGZAG and ZIGZAG PLUS mechanical Prusiks.



EverFlex technology provides great flexibility over time, allowing the rope to maintain excellent handling and optimal performance with devices.



The small size of the splice allows it to pass through the friction chain of the ZIGZAG and ZIGZAG PLUS mechanical Prusiks.

Short Description High-strength, low stretch kernmantle rope with excellent handling for tree care

Selling Points

- Rope designed for tree care:
 - Patented splice at one or two ends for easier rope glide through devices like a friction saver or pulley, and through tree branches
 - Small splice allows the rope to pass through the friction chain of the ZIGZAG and ZIGZAG PLUS mechanical Prusiks
- The large diameter provides great strength and excellent grip
- Consistent performance over time:
 - 100% polyester double weave construction
 - EverFlex technology provides great flexibility over time and under a variety of conditions (water, dust, mud), allowing it to maintain excellent handling and optimal performance with devices
- Available in two colors (green and orange), to help easily identify different work ropes
- Standard lengths: 35, 45, and 60 meters with one splice, and 45 meters with two splices

Specification

- Diameter: 12,5mm
 - Material(s): Polyester
 - Certification(s): CE EN 1891 type A, ANSI Z133
 - Weight per meter: 115g
 - Strength: 30kN
 - Strength tied with figure-eight knot: 15kN
 - Strength with splice: 19kN
 - Impact force (factor 0,3): 5,2kN
 - Number of factor 1 falls: 8
 - Construction: 24 carrier
 - Percentage of sheath: 62%
 - Static elongation: 3,1%
-

Specifications by reference

Reference(s)	R080EA00	R080EA01	R080EA02	R080EA03
Length	35 m	35 m	45 m	45 m
Color(s)	Green	Orange	Green	Orange
	1 splice	1 splice	1 splice	1 splice
Made in	FR	FR	FR	FR
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	4	4	4	4
EAN	3342540850514	3342540850521	3342540850538	3342540850545

Reference(s)	R080EA04	R080EA05	R080DA00	R080DA01
Length	60 m	60 m	45 m	45 m
Color(s)	Green	Orange	Green	Orange
	1 splice	1 splice	2 splices	2 splices
Made in	FR	FR	FR	FR
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	2	2	4	4
EAN	3342540850552	3342540850569	3342540849389	3342540849396

Related product(s)

- ZIGZAG®
- ZIGZAG® PLUS
- TREESBEE®
- NAJA
- EJECT
- FLOW 11.8 mm